

# LED Canopy Light

5-Wattages + 3-CCT, Wet Rated, 135 lm/W, Dimmable + Smart



## FEATURES

<b>Lumen Output</b>	4050 to 13500
<b>Wattage</b>	5-WATT (100W Max)
<b>Efficacy</b>	135 lm/W
<b>Input Voltage</b>	120-277V
<b>Dimmable</b>	0-10V Continuous
<b>CCT</b>	3-CCT (35K, 40K, 50K)
<b>Color</b>	Bronze
<b>Rating</b>	Wet Location
<b>Warranty</b>	5 Years

## APPLICATIONS

Premium outdoor luminaire for surface mounting in ceiling spaces less than 25 feet. Suitable for general storage, cold storage, parking garages, and canopies.

## CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

## ELECTRICAL

Input voltages 120-277V with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and 5-Wattages. Operating temperatures -40°F to 113°F (-40°C to 45°C).

## MOUNTING

Surface mounted installation.

## OPTICS

Anti-UV Prismatic Polycarbonate Lens.

## CONTROLS

Installed fixture mounted PIR or Microwave Sensor with Daylight Priority. Remote Control available.

## EMERGENCY

Installed 90 Minute Emergency Backup Battery Driver options available.

## LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

## WARRANTY

5 year exclusive limited warranty.  
LED's rated at 100,000 hours

5-WATT 100W Max Models



PIR Sensor



Microwave Sensor



Remote Control




Emergency Driver



## TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3500K



4000K



5000K



## SPECIFICATIONS

### ENERGY DATA

**Input Voltage:** 120-277V  
**Input Frequency:** 50/60 Hz  
**Wattage:** 5-WATT (100W Max)  
**Power Factor:** >0.9  
**Total Harmonic Distortion (THD):** <10%  
**Operating Temperature:** -40°F to 113°F (-40°C to 45°C)

### LIGHTING DATA

**Lumens:** 4050 to 13500  
**Lumens Per Watt:** 135 lm/W  
**Correlated Color Temperature (CCT):** 3-CCT (35K, 40K, 50K)  
**Dimmable:** 0-10V  
**Color Rendering Index (CRI):** >70  
**L70:** 50000 hours

## ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
VGP04-100/80/60/40/30WY-H-TCP	30W	120-277V	0.28A@120V, 0.12A@277V	4050	135 lm/W	(3500K, 4000K, 5000K)	0-10V	Bronze	10.06"L x 10.06"W x 2.73"H
	40W		0.37A@120V, 0.16A@277V	5400					
	60W		0.55A@120V, 0.24A@277V	8100					
	80W		0.73A@120V, 0.32A@277V	10800					
	100W		0.92A@120V, 0.40A@277V	13500					

### Control

**HD09VR-PH** 12V DC PIR Bi-Level Daylight High Bay 3-Pin Smart Sensor with Rotator Switches  
**HD09VR-MH** 12V DC MW Bi-Level Daylight High Bay 3-Pin Smart Sensor with Rotator Switches  
**HD06R** Sensor Remote Control with LCD Display (HD Series)

### Emergency

**EM8 (BLD-CM08H-150535-8W)** [INSTALLED] Emergency Backup LED Driver, 8W, 90-Min Batter

## PHYSICAL DIMENSIONS

### All Models

10.06"L x 10.06"W x 2.73"H

