



LED Stick PL Retrofit Lamp-Type B

Product Features

6" Can suitable
 5W Stick LED PL lamp-- 13 watt CFL equivalent
 7W Stick LED PL lamp-- 18 watt CFL equivalent

500lumens \ 700lumens

5W \ 7W

80+ CRI

High power factor >0.9

L70 life 50,000hours

Die casting Aluminum heat sink

Operating Temperature -4°F to 105°F

UL damp listed

Use for totally enclosed fixtures

For both wall-mounted and ceiling fixtures

5 years limited warranty



Application

- Wall scones
- Recessed Can Lighting For Down Light
- Step Lighting

Ordering Number Logic

Typical order example: 5PL01GX23LED30S

Model Number	Base	Power	Lumen Output	CCT	Voltage	PF	Suitable Location	Beam Angle	Control
5PL01E26LEDxxS	E26	5W	500Lm	27	120-277VAC 50/60Hz	>0.9	Dry and Damp	260°	Non-Dimming
5PL01GU24LEDxxS	GU24			30					
5PL01G23LEDxxS	G23			3000K					
5PL01GX23LEDxxS	GX23			35					
5PL01G24QLEDxxS	G24Q			3500K					
5PL01G24DLEDxxS	G24D	41							
7PL01E26LEDxxS	E26	7W	700Lm	41					
7PL01GU24LEDxxS	GU24			4100K					
7PL01G23LEDxxS	G23			50					
7PL01GX23LEDxxS	GX23			5000K					
7PL01G24QLEDxxS	G24Q								
7PL01G24DLEDxxS	G24D								

**** G23, GX23, G24D can be compatible with magnetic ballast or line voltage 120-277VAC.

Base option

Unit: inch

5W Stick PL Lamp:

7W Stick PL Lamp:

