

Tunable LED Linear Strip

4-FT and 8-FT Models



The Tunable LED Linear Strip, 130 lm/W, IP44 Wet Location, 0-10V Dimmable, Premium Indoor Luminaire, Smart Sensor Ready.

Illuminate indoor facilities day and night with Tunable technology for 9X Setting Combinations, Select (3500K, 4000K, 5000K), Select 4-FT (25W, 30W, 40W) or Select 8-FT (54W, 60W, 65W). Smart Sensor Ready for daylight, bi-level dimming, and motion detection.

FEATURES

Lumen Output	3250 to 8450 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3500K, 4000K, 5000K) IP Rating IP44
Wet Location	
Size	4-FT, 8-FT
Warranty	7 Years
Life Expectancy	110,000 hours



APPLICATIONS

Premium indoor luminaire for hanging or surface mounting in ceiling spaces less than 25 feet. Suitable for gymnasiums, warehouses, manufacturing, packaging, storage, aisles, work-stations, and covered decks.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. IP44 Wet Location rated for protection against solid objects 1.0mm diameter and greater, splashing water: IEC 60529.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable CCT (3500K, 4000K, 5000K) and Tunable Wattage (4-FT, 25W, 30W, 40W) or (8-FT, 54W, 60W, 65W). Operating temperatures -4°F to 104°F (-20°C to 40°C).

MOUNTING

Aluminum Surface /Chain Hang Mounts standard. Optional V-Hooks and Chains for hanging available.

OPTICS

Anti-UV Frosted Prismatic Polycarbonate Lens.

CONTROLS

Fixture mounted daylight, bi-level dimming, and motion detection sensor available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC, CE and RoHS compliant.

WARRANTY

7 year exclusive limited warranty. View complete product warranty information www.velighting.com



TUNABLE

CORRELATED COLOR TEMPERATURES (CCT)

3500K

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: Select (25W, 30W, 40W), Select (54W, 60W, 65W)

Power Factor: >0.9

Total Harmonic Distortion (THD): <10%

Operating Temperature: -4°F to 104°F (-20°C to 40°C)

LIGHTING DATA

Lumens: Select [3250 (25W), 3900 (30W), 5200 (40W)] or Select [7020 (54W), 7800 (60W), 8450 (65W)]

Lumens Per Watt: 130 lm/W

Color Correlated Temperature (CCT): Select (3500K, 4000K, 5000K)

Dimmable: 0-10V

Color Rendering Index (CRI): >80

L70: 110,000 hours

ORDERING INFORMATION

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions	Weight
VE-TLS-4-40W	4-FT	(25W 30W 40W)	120-277V	0.21A@120V, 0.09A@277V 0.25A@120V, 0.11A@277V 0.33A@120V, 0.14A@277V	3250 3900 5200	130 lm/W	(3500K, 4000K, 5000K)	0-10V	White	47.99"L x 3.56"W x 3.35"H	5.80 lbs
VE-LSPT-8-65W	8-FT	(54W 60W 65W)	120-277V	0.45A@120V, 0.19A@277V 0.50A@120V, 0.22A@277V 0.54A@120V, 0.23A@277V	7020 7800 8450	130 lm/W	(3500K, 4000K, 5000K)	0-10V	White	94.25"L x 3.56"W x 3.35"H	12.00 lbs

Mount	Sensor
VE-HLSVHC	V-Hooks and Chains
(Blank)	Surface /Chain Hang Mounts (Standard)
	421-OSFHU-ITW
	Leviton Passive Infrared Fixture Mount Occupancy Sensor
	(Blank)
	None


ORDERING GUIDE

VE	TLS	4	40W	ETHLSVHC	421-OSFHU-ITW
VE	Group	Size	Wattage	Mount	Sensor

PHYSICAL DIMENSIONS


4-FT Model

47.99"L x 3.56"W x 3.35"H



8-FT Model

94.25"L x 3.56"W x 3.35"H



SHIPPING INFORMATION

Model	Unit	Shipping	Shipping	Quantity
Wattage	Weight	Dimensions	Weight	/Box
4-FT	5.80 lbs	50.00"L x 3.75"W x 3.75"D	37.00 lbs	6
8-FT	12.00 lbs	98.00"L x 3.75"W x 3.75"D	49.00 lbs	4

