

LED MOISTURE PROOF TUBE IP55



PICTURE



ACCESSORIES



Standard



2FT waterproof plug connector cable
(optional)

PRODUCT FEATURES

Application

- Office lighting, meeting room lighting, hall lighting, hotel lighting, super-market and so on.

Optics

- 5 CCT selectable and 3 Watts selectable.

Electrical

- Flicker free, eyesight protection.
- Instant on/off, no noise/UV/shadow.

Certifications

- ETL and DLC are certificated.

Warranty

- Five-year limited warranty.

LED MOISTURE PROOF TUBE IP55

PERFORMANCE DATA

| Model No. | Watt Select. | CCT Select. | Voltage | Lumens | Beam Angle | PC Cover | IP | Size |
|-----------------------------|--------------|----------------------------|------------|---------|------------|----------|------|------|
| VALI-IP55-4FT-40W-65K-MILKY | 40W | 6500K | AC100-277V | 5000 lm | 120° | Milky | IP55 | 4FT |
| AVLI-IP55-4FT-40W-65K-CLEAR | 40W | 6500K | AC100-277V | 5000 lm | 120° | Clear | IP55 | 4FT |
| VTXD-ER120B-F40W-B-T | 10/25/40W | 3000/4000/5000 /5700/6500K | AC100-277V | 6200 lm | 120° | Milky | IP55 | 4FT |
| VTXD-ER240B-F80W-B-T | 24/50/80W | 3000/4000/5000 /5700/6500K | AC100-277V | 12400lm | 120° | Milky | IP55 | 8FT |

DIMENSIONS

unit: mm/inch

The technical drawing shows a side view of the LED tube with dimension lines. Dimension A is the total length, B is the height of the tube, and C is the width of the tube. A cross-sectional view on the left shows the internal components and the width C.

| Watt | A | B | C |
|-----------|---------------|------------|------------|
| 40W | 1175mm/46.26" | 35mm/1.38" | 44mm/1.73" |
| 10/25/40W | 1175mm/46.26" | 35mm/1.38" | 44mm/1.73" |
| 24/50/80W | 2375mm/93.50" | 35mm/1.38" | 44mm/1.73" |

PACKING

| Watt | Outer Carton | QTY/CTN |
|-----------|-------------------------|---------|
| 40W | 1234.94*279.90*189.99mm | 20 pcs |
| 10/25/40W | 1234.94*279.90*189.99mm | 20 pcs |
| 24/50/80W | 2409.95*279.90*189.99mm | 20 pcs |