

LED Vapor Tight Light



Product Description

V.E. Lightins's Vapor Tight use best Poly Carbonate Body, aluminum heat sink, poly carbonate lens, epistar led chips, anti-corrosion painting design. High-performance Replace 80-120W MH/HPS.

Advantage

- ETL, DLC certificate.
- Input voltage 100-277VAC.
- No UV or IR in the beam.
- Easy to install and operate.
- Energy saving, long lifespan.
- Light is soft and uniform, safe to eyes.
- Instant start, NO flickering, NO humming.
- Green and eco-friendly without mercury.
- Output constant current lever can be adjusted through output cable with 1-10V.

*The product can not be connected to a dimming device when it's equipped with Motion Sensor.



Applications

Warehouse, factory and workshops; Exhibition hall and supermarkets, etc



LED Vapor Tight Light

Specifications

Model No.	VE-LED220-SF-DS
Input Power	40W
Lumen	4200-5200LM
Lumen Efficacy	105-130LM/W
Color Temperature	4000K, 4500K, 5000K, 5700K
CRI	>83
Viewing Angle	150°(wall installation), 360°(ceiling installation)
Input Voltage	100-277V / 347V AC 50/60Hz
PF	≥0.95
THD	≤20%
Driver Brand	China brand driver
Optional Accessory	Motion Sensor, PIR Sensor
LED Brand	Epistar
LED Type	SMD2835
LED QTY	288 PCS
Housing	PC body
Housing Color	White
Waterproof Rating	DAMP
Operating Temperature	-40°C TO 40°C
Operating Humidity	20%-90% RH
Storage Temperature	-40°C TO 80°C
Storage Humidity	10%-95% RH
Warranty Time	5 Years

Photometrics

